TECHNICAL INFORMATION SHEET ARGENTIUM 960 CASTING SILVER



Dated: August 2021

GENERAL INFORMATION

COMMERCIAL COMPOSITION **MELTING TEMPERATURES**

Silver: 96.2% 920°C / 1688°F Liquidus: Solidus: 890°C / 1634°F Copper Germanium Melting range: 30°C / 86°F

FULL CHARACTERISATION DATA

COLOUR COORDINATES

L*	95.7	
A*	-0.3	
B*	3.5	
C*	3.5	
Yellow Index	6.3	

AS CAST GRAIN SIZE [µm]: 190

DENSITY [g/cm³]: 10.4

PRODUCT APPLICATIONS

Casting in open systems Casting in closed systems Casting without stones Stone-in-place casting

MECHANICAL CHARACTERISTICS

55
155
55
100
120
227
147
36

IMPORTANT: MAXIMISING ARGENTIUM SILVER'S TARNISH RESISTANCE

To initiate and optimise tarnish resistance, a grease-free surface must be achieved as a final finishing process - see 'CLEANING & RINSING' instructions, page 2.

TECHNICAL INFORMATION SHEET ARGENTIUM 960 CASTING SILVER

ARGENTIUM®
THE FINEST SILVER

Dated: August 2021

CASTING PROCESSING PARAMETERS

CASTING TEMPERATURES	Flask from [°C / °F]	Flask to [°C / °F]	Metal from [°C / °F]	Metal to [°C / °F]
Less than 0.5mm:	600 / 1112	640 / 1184	1020 / 1868	1050 / 1922
0.5 - 1.2mm:	560 / 1040	600 / 1112	1000 / 1832	1020 / 1868
More than 1.2mm:	540 / 1004	580 / 1076	980 / 1796	1000 / 1832

CASTING ATMOSPHERE: Melt under an inert atmosphere (nitrogen or argon).

CASTING TREES WITHOUT STONES: Let the flask cool down in the chamber for 1 minute after pouring. Take the

flask out of the machine without shaking it, let it cool for 20 minutes in air, then

quench in water.

STONE-IN-PLACE CASTING TREES: Let the flask cool down for 30-45 minutes, then guench in water.

REMELTING / RECYCLING: 50:50 old/new material. Ensure previously cast Argentium is clean and free of

investment residues.

PICKLING: 10% Sulphuric Acid solution or Sodium Bisulphate, weak Sparex, Phosphoric Acid (diluted as per

supplier's instructions). Keep pickling time to a minimum. Do NOT use Hydrofluoric Acid.

PRECIPITATION HARDENING PARAMETERS

SINGLE STEP PRECIPITATION HARDENING TREATMENT	Temp. [°C / °F]	Time	Cooling
Heat harden in air atmosphere:	300 / 572	90 mins	Slow cool in air or in furnace
DOUBLE STEP PRECIPITATION HARDENING TREATMENT	Temp. [°C / °F]	Time	Cooling
	.op.[o / .]	111110	Cooming
Step 1: Heat in a protective atmosphere:	700 / 1292	40 mins	Quench in water *

HEAT/COLOUR RECOGNITION & COOLING ARGENTIUM SILVER

Argentium Silver glows a paler colour than standard Stering silver at red-hot temperatures. Take care not to overheat the metal. (Temperature/metal colour recognition is easier to judge working in a shaded area.)

*Argentium Silver retains its heat for longer than standard Sterling silver - allowances for a slower cool must be made when quenching.

FINISHING PROCESSES

POLISHING

Argentium Silver can be polished using traditional wheels or mass finishing processes. The use of separate polishing wheels for Argentium Silver items is advised - this prevents cross-contamination of another metal/alloy onto the surface of Argentium pieces, which can compromise tarnish resistance.

CLEANING & RINSING

To maximise Argentium Silver's tarnish resistance, a grease-free surface must be achieved using ultrasonic cleaning. We do **NOT** recommend electrolytic cleaning or steam cleaning.

Use of distilled water for cleaning / rinsing is recommended to prevent water marks. Please do NOT use deionised / reverse osmosis water with Argentium Silver.

NB. For high volume production, please refer to 'Argentium Cleaning Guidelines' document by Legor Group.